# #115

# 3-PLY 330# 1/8 X 1/16 APACHE POWERCLEAT™ WITH 1/2" HIGH X 6" OVERALL WIDTH MOLDED CRESCENTS



### **FEATURES**

The Apache PowerCleat™ is a 1/2" crescent cleat profile, designed to significantly increase carrying capacity when compared to conventional multichevron belts. The cleat height and crescent profile allow for greater conveyor incline angles over a larger variety of applications and conveyed product. The crescent shape was designed for better flex when discharging, allowing for a cleaner discharge of material with less carryback. Additionally, the overlapping pattern creates less noise and chatter on return rollers.

## **APPLICATIONS**

- Recycling
- Wood Processing
- Road Construction
- Grain Handling

#### **SPECIFICATIONS**

Plies	3
<b>Working Strength</b>	330
Color	Black
Material	NBR Blend
Carcass	Polyester/Nylon
Top Cover	Molded Crescent
<b>Bottom Cover</b>	Smooth
Profile	1/2" High x 5/8" Wide x 6" Overall Width Crescent
Thickness	17/64"
Weight PIW	0.287
Min. Pulley Diameter	16"
Max. Elongation	1-2%
Temperature Range	-25°F to 250°F
Fire Resistant	No
Oil Resistant	Yes
Anti-Static	No
Durometer	65 +/- 5

#### RECOMMENDED SPLICE

Flexco® Bolt Solid Plate	190
Flexco® Bolt Rivet Plate	BR6
Flexco® Rivet Hinge	R2
Super-Screw®	63, 65
<b>Endless Splice</b>	Bias Step

