

# #116

## 3-PLY 330# 1/8 X BARE APACHE POWERCLEAT™ WITH 1/2" HIGH X 6" OVERALL WIDTH MOLDED CRESCENTS



### FEATURES

The Apache PowerCleat™ is a 1/2" crescent cleat profile, designed to significantly increase carrying capacity when compared to conventional multi-chevron belts. The cleat height and crescent profile allow for greater conveyor incline angles over a larger variety of applications and conveyed product. The crescent shape was designed for better flex when discharging, allowing for a cleaner discharge of material with less carryback. Additionally, the overlapping pattern creates less noise and chatter on return rollers.

### APPLICATIONS

- Recycling
- Road Construction
- Wood Processing
- Grain Handling

### SPECIFICATIONS

Plies	3
Working Strength	330
Color	Black
Material	NBR Blend
Carcass	Polyester/Nylon
Top Cover	Molded Crescent
Bottom Cover	Bare
Profile	1/2" High x 5/8" Wide x 6" Overall Width Crescent
Thickness	21/64"
Weight PIW	0.254
Min. Pulley Diameter	16"
Max. Elongation	1-2%
Temperature Range	-25°F to 250°F
Fire Resistant	No
Oil Resistant	Yes
Anti-Static	No
Durometer	65 +/- 5

### RECOMMENDED SPLICE

Flexco® Bolt Rivet Plate	BR6
Flexco® Rivet Hinge	R2
Super-Screw®	63, 65
Endless Splice	Bias Step