
TT CONVEYANCE SOLUTIONS.

MiConveyanceSolutions.com



Large Distribution Center

SOLUTIONS BROCHURE



Package Handling **Process**

Moving Forward

From live roller and incline conveyors to merge-and-divert conveyors, Motion Conveyance Solutions understands the complexity each application requires to ensure maximum life and product performance in your distribution center.

Offering Features

Induction

Improved Delivery Locally Committed Inventories

Ease of Ordering 24-Hour Service

The Solutions You Need with Service You Can Trust

When there is product on the move, you need something reliable that will stand up to long run times. Whether you're moving paper-based containers or something more durable like plastic, Motion Conveyance Solutions has the conveying products you need.

Live Roller Conveying Merge/Accumulation

High-Grip Conveying

General Conveying

Diverter Gapper Incline/Decline

Lightweight Belting Solutions



#5045: PVC 120 BLK COS

- General Conveying
- Horizontal Conveying
- Economical Conveying




#4391: TM120RT-B

- General Conveying
- Horizontal Conveying
- · Economical Conveying



#4395: 2PM5LK-NP

- Friction Cover
- Negative Pyramid
- Whisper Weave Fabric



#4390: PHR-135-BBXBB

- Accumulation/Merge
- Bare Bottom
- Horizontal Conveying



#5040: PVC 120 BLK FBS

- Low Friction
- Horizontal Conveying
- Accumulation/Merge



#4340: TM120LR-B

- · Friction Cover
- Longitudinal Groove
- Non-Woven



#4128: 2PM10BLK-BBXBB

- Accumulation/Merge
- Bare Cover
- Whisper Weave Fabric



#4126: PHR3-200 BBXBB

- · Accumulation/Merge
- Bare Bottom
- Horizontal Conveying



#4321: PVC 120 BLK R/T

- Incline/Decline Conveying
- Rough Top Cover
- Economical Conveying



#4136: TIM120FBS-B

- Low Friction
- · Accumulation/Merge
- Non-Woven



#4141: 2PM8BLK-COS MAT

- Matte PVC Cover
- Bare Bottom
- Horizontal Conveying




PHR3-265 BBXBB

- Accumulation/Merge
- Bare Bottom
- Horizontal Conveying



#4301: 2PLY 150 BLK R/T

- · Incline/Decline Conveying
- Rough Top Cover
- · Abrasion Resistant



#4328: 2PM10BLK-LG

- · Friction Cover
- Longitudinal Groove
- · Whisper Weave Fabric



NHM-10EKBV

- Matte PVC Cover
- Bare Bottom
- Horizontal Conveying



FL750 - TA-12BK

- TPU
- Segmented Conveyors
- Elastic TPU



#4339: 2PLY 100 RED LG

- · Incline/Decline Conveying
- Rubber Cover
- · Very Abrasion Resistant



#4393: 2PM10BLK-NP

- Friction Cover
- Negative Pyramid
- Whisper Weave Fabric



SNTC

- · Induction Belts
- High-Grip Cover
- Elastic TPU



TC

- TPU
- Segmented Conveyors
- Elastic TPU

MiConveyanceSolutions.com

Belt-Driven Roller Conveyors

Distribution centers, warehouses, fulfillment centers, cross-dock facilities, and delivery centers are always on the move. Various belting applications are integral to these package handling facilities, and Motion Conveyance Solutions offers unique solutions up to the challenge of constant runtime.

Locally Committed Inventories

Flexco® Aero 325 Press



- 110 V power, quickly cycles up to temperature
- Cooled by air
- 12-19 minute cycle time
- Reduces replacement time by almost 45 minutes

45 mm Press - Mi Item #: 08905191 77 mm Press - Mi Item #: 08544270

Flexco® Pun M NDX Cutter



- Delivers precision with every cut
- Prepare belt ends in 3-5 minutes
- Fully automatic indexing for easy and accurate preparation
- Cuts up to 200 mm wide belts

114 mm Cutter - Mi Item #: 09658210 200 mm Cutter - Mi Item #: 09658212

NoviTool RedDrive Workstation



- Will hold up to 52" diameter roll of belt
- Will allow you to dispense the belt from the unit
- · Adjustable back plate to keep belt roll aligned
- Drawers to hold each silicone template

Workstation Only - Mi Item #: 14232969

RedDrive® 45 mm

Exclusive to Motion Conveyance Solutions, the 45 mm RedDrive belt was developed to replace the commonly used blue drive belt. With increased strength and a harder surface, RedDrive boasts improved flexibility and better grip than the blue drive belt. Our improved belt can be spliced with existing equipment or can be equipped with a 200 mm long splice for ease of installation.

Mi Item #: 08544550





RedDrive® 77 mm

Kevlar® technology, combined with a more durable TPU compound, not only delivers a stronger, lighter belt but requires 25% less tension to drive. Exclusive to Motion Conveyance Solutions, this belt delivers an easier splice, is less noisy, and is 30-40% more durable than the OEM product.

Mi Item #: 08544369

Lacing and **Fasteners**









AND PIN SIZE S	ELECTION CH	ART							
		BELT THICKNESS							
WIRE DIAMETER		UP TO 3/64" (0.047")	1/16" (0.063")	3/32" (0.093")	1/8" (0.125")	5/32" (0.156")	3/16" (0.188")	7/32" (0.219")	
IN.	MM	1.2 mm	1.6 mm	2.4 mm	3.2 mm	4.0 mm	4.8 mm	5.6 mm	
0.03	0.06	25SP							
0.03	0.06	25*							
0.036 x 0.027	0.9×0.7	UCM36SL XSP							
0.036 x 0.027	0.9 x 0.7		UCM36SL	SP					
0.036 x 0.027	0.9 x 0.7	UCM36 XSP							
0.036 x 0.027	0.9 x 0.7		UCM36 SP	*					
0.036 x 0.027	0.9 x 0.7		36 SP*						
0.04	1.0		1 XSP*						
0.04	1.0		UX-1 SP*						
0.036 x 0.027	0.9 x 0.7			UCM36*					
0.036 x 0.027	0.9 x 0.7			36*					
0.04	1			1 SP*					
0.036 x 0.027	0.9 x 0.7				UCM36 LP*				
0.04	1				1*				
0.04	1				UX-1*				
0.05	1.4				U2 SP				
0.05	1.4				2SP				
0.05	1.4					U2			
0.00						-			
	IN. 0.03 0.03 0.036 × 0.027 0.036 × 0.027 0.036 × 0.027 0.036 × 0.027 0.036 × 0.027 0.036 × 0.027 0.04 0.04 0.04 0.036 × 0.027 0.04 0.04 0.036 × 0.027 0.04 0.04 0.036 × 0.027 0.04 0.05	N. MM 0.03 0.06 0.06 0.03 0.06 0.06 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.04 1.0 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.05 1.4 0.05 1.4 0.05 1.4 0.05 1.4	WIRE DIAMETER UP TO 3/64" (0.047") IN. 0.03 0.06 25SP 0.03 0.06 25* 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.04 0.04 0.04 0.04 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.04 1.0 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.05 1.4 0.05 1.4	WIRE DIAMETER WIRE DIAMETER UP TO 3/64" (0.047") IN. MM 1.2 mm 1.6 mm 0.03 0.06 25\$P 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.04 1.0 0.04 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.036 × 0.027 0.9 × 0.7 0.04 1.0 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.036 × 0.027 0.9 × 0.7 0.04 1 0.05 1.4 0.05 1.4	WIRE DIAMETER BELT THICKNESS UP TO 3/64" (0.047") (0.063") (0.093") IN.	WIRE DIAMETER Description	WIRE DIAMETER BELT THICKNESS UP TO 3/64" (0.047") (0.063") (0.093") 1/8" (0.125") 5/32" (0.156") IN.	WIRE DIAMETER Description of the process of the	

ALLIGATOR READY SET ST	APLE FASTENER SELECTION (GUIDE				
FASTENER SIZE	FOR BELTS WITH MECHANICAL UP TO:	FASTENER RATING	BELT THICKNES	SS RANGE	RECOMMENDE PULLEY DIAME	TER
	PIW	KN/M	IN.	MM	IN.	MM
62	100	17	1/16-1/8	1.5-3.2	2	50
125	160	28	1/8-3/16	3.2-4.8	3	75
187	200	35	3/16-1/4	4.9-6.4	4	102

LACING SIZE	FOR BELTS WITH MECHANICAL FASTENER RATING UP TO:		BELT THICKNESS RANGE		RECOMMENDED MINIMUM PULLEY DIAMETER		APPROX. CORRUGATED HINGE PIN DIAMETER	
	PIW	KN/M	IN.	MM	IN.	MM	IN.	MM
0	25	4.3	Up to 1/16	Up To 1.6	1	25	3/64	1.2
1	45	7.8	1/16-3/32	1.6-2.4	1 - 1/2	38	1/16	1.6
7	50	9.7	3/32-9/64	2.4-3.6	2	51	1/16	1.6
15	65	11.4	1/8-5/32	3.2-4.0	2 - 1/2	64	3/32	2.4
20	95	16.6	5/32-3/16	4.0-4.8	3	76	7/64	2.8
25	100	17.5	3/16-7/32	4.9-5.6	4	102	1/8	3.2
27	100	17.5	7/32-9/32	5.6-7.1	5	127	1/8	3.2

^{*}Special installation of plastic spiral lacing available through our fabrication centers.

Flexco® Installation Tools and Accessories

Whether your application dictates your lacing style or you have a preferred style, there are many tools and accessories to ensure your lacing gets installed with accuracy and efficiency.







SmartClamp™ Belt Clamps



Alligator® Ready Set™ Staple Installation Tool



Flexco® Belt Cutter



Clipper® Roller Lacer

Clipper® Roller Lacer Features and Benefits









- **A.** Lacer Head moves roller shaft with manual handle or cordless drill, offering less operator fatigue and faster installation
- **B.** Storage slots provide secure access to storage of lacing strips
- **C.** Clevis Bracket and Guide Rollers provide holding force for embedding the hooks into the belt with additional stability
- D. Face Strip and Clamping Design hold hooks during installation, guiding the belt and offering easier, reduced installation time

MiConveyanceSolutions.com

MiConveyanceSolutions.com

Expect More with **Motion**

Less Stress, More Uptime

With Motion Conveyance Solutions, a single PO can cover multiple applications and product lines—helping reduce overhead and paperwork. It also makes qualifying for freight discounts easier, significantly reducing transportation costs.

With local inventory in our 40+ belt shops throughout the US, we are dedicated to your business with service available 24/7. As your partner, Motion Conveyance Solutions can consolidate your supplier base and increase efficiencies—all while dramatically reducing your downtime.

Plus, Motion OEM part numbers and products have already been identified on almost everything.

Proven Experience

- Experts who understand your challenges
- A partner committed to your success 24/7/365
- A proven market leader with a global reach
- 75+ years of dedication to quality products tested and proven to withstand the toughest applications

After Hours


Available 24/7/365

Over 600 Locations

Access to All Motion Products

Motion Subject Matter Experts

Transportation Experts





Motion Conveyance Solutions—

Belting, Hose, Gaskets, Seals, Urethane, and Custom Cut Parts

Scan Here

To find shops and services closest to your location.



