

MOTION CONVEYANCE SOLUTIONS HW BELT

20003985 3-PLY 330# 1/4" X 1/16" HC 710



FEATURES

Premium high-temperature heat-resistant belt. This 3-ply 330# belt features a 1/4" smooth top cover with a poly/nylon carcass and a 1/16" smooth bottom. Designed for superior crack resistance to protect the carcass. This belt can withstand temperature spikes up to 752°F.

APPLICATIONS

- Clinker
- Coke
- Dried Clay
- Dried Lime
- Sintered Ore Products
- Taconite

SPECIFICATIONS

Plies	3
Working Strength	330
Color	Black
Material	Rubber
Carcass	Poly/Nylon
Top Cover	Smooth
Bottom Cover	Smooth
Profile	N/A
Thickness	0.462"
Weight PIW	0.217
Min. Pulley Diameter	22"
Elongation @ 100%	1-2%
Temperature Range	140°F – 752°F
356°F for max fines, 752°F for bulk material temp	
Fire Resistant	No
Oil Resistant	No
Antistatic	No
Durometer	60+/-5 Shore A

RECOMMENDED SPLICE

Flexco® Bolt Solid Plate	190
Flexco® Ready Bolt Rivet Plate	BR6
Flexco® Bolt Hinge	550
Flexco® Rivet Hinge	R5
Super-Screw®	63
Endless Splice	Bias Step