

MOTION CONVEYANCE SOLUTIONS HW BELT

#407 20003986 2-PLY 220# 3/16" X 1/16" HC 710



SPECIFICATIONS

Plies	2
Working Strength	220
Color	Black
Material	Rubber
Carcass	Poly/Nylon
Top Cover	Smooth
Bottom Cover	Smooth
Profile	N/A
Thickness	0.346"
Weight PIW	0.162
Min. Pulley Diameter	16"
Elongation @ 100%	1-2%
Temperature Range	140°F – 752°F
356°F for max fines, 752°F for bulk material temp	
Fire Resistant	No
Oil Resistant	No
Antistatic	No
Durometer	60+/-5 Shore A

RECOMMENDED SPLICE

Flexco® Bolt Solid Plate	140
Flexco® Ready Bolt Rivet Plate	BR6
Flexco® Bolt Hinge	375
Flexco® Rivet Hinge	R2
Super-Screw®	63
Endless Splice	Bias Step

FEATURES

Premium high-temperature heat-resistant belt. This 2-ply 220# belt features a 3/16" smooth top cover with a poly/nylon carcass and a 1/16" smooth bottom. Designed for superior crack resistance to protect the carcass. This belt can withstand temperature spikes up to 752°F.

APPLICATIONS

- Clinker
- Coke
- Dried Clay
- Dried Lime
- Sintered Ore Products
- Taconite